



**Product:** [SPIDER II 8TX PoE](#)

Unmanaged 8-port Switch with PoE support

**Product Description**

Unmanaged Industrial Ethernet DIN Rail Mount Switch with PoE support, store and forward switching mode, 8 x 10/100 Mbit/s RJ45

**Technical Specifications**

**Product description**

Type:	SPIDER II 8TX PoE
Name:	SPIDER II 8TX PoE
Description:	Entry Level Industrial Ethernet Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
Part Number:	942008001
Port type and quantity:	8 x 10/100BASE-TX, 4 x PoE according to IEEE802.3af, TP-cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity

**More Interfaces**

Power supply/signaling contact:	1 x plug-in terminal block, 3-pin, no signaling contact
---------------------------------	---

**Network size - length of cable**

Twisted pair (TP):	0-100 m
--------------------	---------

**Network size - cascability**

Line - / star topology:	any
-------------------------	-----

**Power requirements**

Operating Voltage:	18 V DC - 32 V DC
Operating voltage DC:	9.6 V DC - 32 V DC
Power consumption:	max. 75 W
Power output in BTU (IT)/h:	234.2

**Diagnostics features**

Diagnostic functions:	LEDs (power, link status, data, data rate)
-----------------------	--

**Ambient conditions**

MTBF (Telecordia SR-332 Issue 3) @ 25°C:	479015 h
Operating temperature:	-10-+60 °C
Storage/transport temperature:	-20-+70 °C
Relative humidity (non-condensing):	10-95 %

**Mechanical construction**

Dimensions (WxHxD):	35 mm x 138 mm x 121 mm
Weight:	560 g
Mounting:	DIN Rail, Wall mounting
Protection class:	IP30

**Mechanical stability**



IEC 60068-2-6 vibration:	3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
IEC 60068-2-27 shock:	15 g, 11 ms duration, 18 shocks

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field:	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst):	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage:	power line: 2 kV (line/earth), 1 kV (line/line), 2 kV data line
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz-80 MHz)

EMC emitted immunity

EN 55032:	EN 55032 Class A
EN 55022:	EN 55022 Class A
FCC CFR47 Part 15:	FCC 47CFR Part 15, Class A

Approvals

Safety of industrial control equipment:	cUL 508
Employment in vehicles:	E1

Scope of delivery and accessories

Accessories to Order Separately:	Rail power supply RPS 80 EEC or RPS 120 EEC, 19" installation frame
Scope of delivery:	Device, terminal block, operating manual

Further Instructions

Product Documentation:	<a href="https://www.doc.hirschmann.com">https://www.doc.hirschmann.com</a>
Certificates:	<a href="https://www.doc.hirschmann.com/certificates.html">https://www.doc.hirschmann.com/certificates.html</a>

Variants

Item #	Type
942008001	SPIDER II 8TX PoE

Update and Revision:	Revision Number: 0.108 Revision Date: 08-17-2022
----------------------	--

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.